



A High-Performance, All-Purpose Can Liner

Can Liners

Linear Low Density-LLDPE

ThickSkins™ Ultra

FEATURES

- Made with proprietary formulas using prime virgin resins.
- Excellent strength with solid puncture and tear resistance.
- Seamless tubular construction.
- Leak-proof star seal.
- Choose from a wide range of sizes in Clear, Black or White.
- Available in 0.34 – 2.00 MIL gauges for regular to heavy-duty use.
- Coreless rolls for ease of use and storage.



ThickSkins Ultra can liners are a great all-purpose waste-containment solution for industrial, commercial and institutional applications. These versatile bags efficiently handle everything from paper and general refuse to heavy or sharp waste.

With excellent load capacity, tear resistance and toughness, ThickSkins™ Ultra can liners out-perform competitive low-density bags in virtually every application. This jack-of-all-trades can liner is a smart choice that delivers total confidence every time you use it.



Can Liner Specifications

ThickSkins™ Ultra Linear Low Density-LLDPE

BLACK	Item Number		SIZE	GALLONS	MIL	ROLL/BAGS	COUNT	NET CASE WT / LBS
	CLEAR	WHITE						
-	BKC1718L	-	17 x 18	4	0.34	10/200	2000	13.9
BKK2022L	BKC2022L	-	20 x 22	7	0.34	10/100	1000	10.0
BKK2424L	BKC2424L	-	24 x 24	7-10	0.36	10/100	1000	13.8
-	BKC2424R	-	24 x 24	7-10	0.47	10/100	1000	18.0
BKK2424M	BKC2424M	-	24 x 24	7-10	0.74	10/50	500	14.2
BKK2433L	BKC2433L	-	24 x 33	12-16	0.36	10/100	1000	19.0
BKK2433R	BKC2433R	BKW2433R	24 x 33	12-16	0.47	10/50	500	12.4
BKK2433M	BKC2433M	-	24 x 33	12-16	0.72	10/50	500	19.0
BKK2433XMP	-	BKW2433XMP	24 x 33	12-16	0.98	10/25	250	12.9
-	BKC2745XMP*	-	27 x 45	23	1.00	10/25	250	20.1
-	-	BKW2643H	26 x 43	30	1.13	4/25	100	8.40
BKK3037R	BKC3037R	-	30 x 37	20-30	0.51	10/50	500	18.9
BKK3037HR	BKC3037HR	-	30 x 37	20-30	0.59	10/25	250	10.9
BKK3037M	BKC3037M	-	30 x 37	20-30	0.71	5/50	250	13.2
BKK3037MP	BKC3037MP	-	30 x 37	20-30	0.97	10/25	250	18.0
-	BKC3037H	-	30 x 37	20-30	1.14	8/25	200	16.9
BKK3340R	BKC3340R	-	33 x 40	33	0.52	5/50	250	11.5
BKK3340HR	-	-	33 x 40	33	0.59	10/25	250	13.0
BKK3340M	BKC3340M	BKW3340M	33 x 40	33	0.70	10/25	250	15.4
BKK3340XMP	BKC3340XMP	BKW3340XMP	33 x 40	33	0.98	8/25	200	17.3
-	BKC3340H	BKW3340H	33 x 40	33	1.14	6/25	150	15.1
-	BKC3340HP	-	33 x 40	33	1.30	10/10	100	11.4
-	BKC3340XH	-	33 x 40	33	1.50	5/20	100	13.2
BKK3658M	BKC3658M	-	36 x 58	55	0.75	8/25	200	20.9
BKK3658MP	BKC3658MP	-	36 x 58	55	0.97	5/20	100	13.5
BKK3858M	BKC3858M	BKW3858M	38 x 58	60	0.74	8/25	200	21.8
BKK3858MP	BKC3858MP	-	38 x 58	60	0.97	5/20	100	14.3
-	BKC3858XMP	-	38 x 58	60	1.05	10/10	100	15.4
BKK3858H	BKC3858H	BKW3858H	38 x 58	60	1.18	10/10	100	17.3
BKK3858HP	BKC3858HP	-	38 x 58	60	1.30	10/10	100	19.1
-	BKC3858XH	-	38 x 58	60	1.50	10/10	100	22.0
-	BKC3858UH	-	38 x 58	60	2.00	5/10	50	14.7
-	BKC4048R	-	40 x 48	40-45	0.56	10/25	250	17.9
-	-	BKW4048M	40 x 48	40-45	0.73	8/25	200	18.7
BKK4048XMP	BKC4048XMP	BKW4048XMP	40 x 48	40-45	0.98	6/25	150	18.8
-	-	BKW4048H	40 x 48	40-45	1.15	5/20	100	14.7
BKK4048HP	BKC4048HP	BKW4048HP	40 x 48	40-45	1.30	10/10	100	16.6
-	BKC4048XH	-	40 x 48	40-45	1.50	10/10	100	19.2
-	BKC4048UH	-	40 x 48	40-45	2.00	10/10	100	25.6
BKK4154XMP	-	-	41 x 54	40-50	0.99	5/20	100	14.6
BKK4348M	-	-	43 x 48	56	0.72	6/25	150	14.9
BKK4348XMP	BKC4348XMP	BKW4348XMP	43 x 48	56	0.99	10/15	150	20.4
-	-	BKW4348H	43 x 48	56	1.18	5/20	100	16.3
BKK4348HP	-	-	43 x 48	56	1.30	10/10	100	17.9
-	BKC4348XH	-	43 x 48	56	1.50	10/10	100	20.6
-	BKC4348UH	-	43 x 48	56	2.00	10/10	100	27.5
BKK4650M	BKC4650M	-	46 x 50	65	0.85	4/25	100	13.0

*= Sized-to-Fit

Specifications subject to change without notice.

The Pro-Link difference.

The first time you try a Pro-Link can liner you'll discover that the difference is real. We follow an exacting formula for manufacturing and use only the highest grade resins to manufacture the best liner films. Our films are thinner and stronger, and have consistently set the standard in the industry. Gauge-for-gauge, our liners are stronger than any others, and provide consistent and reliable containment for a wide range of applications.

You are what you make.

From lightweight liners used in offices, to super-strong trash bags intended for the most demanding industrial waste, Pro-Link bags are built to perform. Our linear tube construction process takes place in a precisely climate-controlled environment. This allows us to maintain the exact manufacturing conditions needed to produce varying sizes and types of bags with no flaws or irregularities in the material.

We select our resins using an extremely narrow range of parameters, always adhering to our own standards for consistency.

Our automated lines are monitored using sophisticated sensors that alert us immediately to potential problems and ensure total consistency in manufacturing. Using only prime virgin resin allows us to make a stronger, more dependable trash bag.

- **Seamless tubular construction maximizes overall integrity.**
- **Star-seal bottom eliminates seam failure and prevents leaks.**
- **Premium resins deliver run-to-run consistency and reliable bag performance.**
- **Continuous quality testing ensures optimum performance and reliability.**
- **Use of less material reduces the solid waste that goes into landfills.**

Distributed by: