




# Safety Data Sheet

## Urethane Fortified Finish

### Section 1. Identification

Product Identifier	Urethane Fortified Finish		
Synonyms	N/A		
Manufacturer Stock Numbers	N/A		
Recommended use	Floor Polish		
Uses advised against	N/A		
Manufacturer Contact Address	Pro Link 510 Chapman Street Canton , MA, 02021 USA		
	Phone	Emergency Phone	Fax
	N/A	(866) 303-0648	N/A

### Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 5 ACUTE TOXICITY - ORAL - Category 5
Signal Word	Warning
Pictogram	
Hazard Statements	May be harmful if swallowed May be harmful in contact with skin
Precautionary Statements	
Response	If swallowed: Immediately call a poison center/doctor.
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.
Storage	Store in a dry place. Store in a closed container.

Disposal	Dispose of contents/container in accordance with local/regional/international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	No Data Available

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
111-90-0	Glycol Ether DE	6 %

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

Eye	Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
Skin	Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

### Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
Unsuitable Extinguishing Media	N/A
Flammable Properties	Will burn if involved in a fire.

### Section 6. Accidental Release Measures

SMALL SPILLS	Absorb with an inert solid and scoop up for disposal, then rinse soiled area with water.
LARGE SPILLS	Stop leak at source and collect into suitable container, then treat as a small spill.

## Section 7. Handling and Storage

### Storage

Keep away from food and drinking water. Keep container closed to prevent drying out. Store in a cool place in original container and protect from sunlight.

### Handling

Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

## Section 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Glycol Ether DE	N/A	N/A	N/A

### Personal Protective Equipment 202

Goggles, Gloves, Apron, SYNTHETIC APRON

Eyes: Safety glasses or goggles.

Skin: Nitrile or polyethylene gloves and aprons. Do not use cotton.

Ventilation: Positive down-draft exhaust ventilation should be provided to maintain vapor concentration below TLV.

Respiratory: Not available

## Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	White/Opaque
Odor	Acrylic Polymer
Odor Threshold	N/A
Solubility	Emulsion
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	N/A
Specific Gravity	1.04
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	N/A
FP Method	N/A
Ph	8.0-9.0
Melting Point	N/A
Boiling Point	209 Deg. F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	N/A
Vapor Density	N/A

## Section 10. Stability and Reactivity

### Stability

Chemical Stability: Stable  
Conditions to Avoid: Temperature Extremes  
Incompatibility: None  
Hazardous Decomposition: Will not occur  
Hazardous Polymerization: Will not occur

## Section 11. Toxicological Information

**Toxicological Information** Primary Route(s) of Entry: Skin contact /absorption and inhalation  
Signs and Symptoms of Overexposure: Gastrointestinal irritation (nausea, vomiting, diarrhea), irritation to nose, throat, and respiratory tract.  
Target Organ Effects: Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals and may aggravate pre-existing disorders or these organs in humans: chronic ingestion may cause kidney and liver lesions at high doses.  
IMMEDIATE HEALTH EFFECTS:  
EYES: Exposure may cause noticeable pain, and severe irritation.  
SKIN: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking and skin burns. Additional symptoms of skin contact may include: allergic reaction. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal handling and use.  
INHALATION: Exposure to vapor or mist is possible. Short term inhalation is not likely to cause harmful effects: breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits.  
INGESTION: Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects: swallowing large amounts may be harmful.  
REPRODUCTIVE / DEVELOPMENTAL INFORMATION:  
No Data  
CARCINOGENIC INFORMATION: This material is not listed as a carcinogen by IARC, NTP, or OSHA  
LONG TERM EFFECTS: No Data

## Section 12. Ecological Information

No Data Available

## Section 13. Disposal

**WASTE DISPOSAL METHOD:** For proper disposal of waste, refer to federal and state regulations.

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	Non Hazardous
Packing Group	N/A

## Section 15. Regulatory Information

### Regulatory Statement

US Federal Regulations  
TSCA (Toxic Substances Control Act) Status  
TSCA (United States) The intentional ingredients of this product are listed.  
CERCLA RQ - 40 CFR 355 Appendix A:None  
SARA 302 Components 40 CFR Appendix A: None  
Section 311/312 Hazard Class 40 CFR 370.2  
Immediate (X) Delayed (X) Fire ( ) Reactivity ( ) Sudden Release of Pressure ( )  
SARA 313 Components - 40 CFR 372.65  
\* Listed in Section 2 as Diethylene Glycol Monomethyl Ether  
State and Local Regulations  
California Proposition 65: None  
California SCAQMD Rule 443.1 VOC's: > 100g/L  
North Carolina Administrative Code 2D.1104 and 2B.0610 None  
South Carolina Regulation 62.5 Standard Number 8: None

## Section 16. Other Information

### Revision Date

5/7/2015

### DISCLAIMER:

The information contained herein is believed to be accurate and is offered in good faith. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Mixing this product with any other materials may change the characteristics such as flash point, flammability or health effects. Because product use is beyond our control, no warranty is given, expressed or implied.